

FT2-07 Series 4 Colour Ink

[Product description]

This product is suitable for fast printing speed (12000 revolution per hr), can be printed on coated paper, white board paper, wood free paper. Printing application include album, poster, advert, logo, manual etc. packaging. Suitable for mono colour, duo colour, 4 colour, 5 colour and 6 colour printer

[Product characteristic]

- ❖ Good printing adaptability and good colour reproduction
- ❖ High colour saturation, high transfer density and clear printing dot
- ❖ Ink unlikely to form peel during printing, fast drying speed can avoid printed surface from catching dirt
- Good rub resistance

Technical parameter

Test		FT2307 Yellow	FT2407 Red	FT2507 Blue	FT2107 Black
TV		7.5-8.5	8.5-9.5	8.5-9.5	9-10.5
DM mm		36-38	37-39	36-38	37-39
GM μ		<15	<15	<15	<15
Colour		Close to standard			
Drying speed	Paper	<5	<5	<5	<5
(Hr)	Film	24-72	24-72	24-72	24-72
Light fastness		3	5	7	7
Acid resist.		5	3	5	5
Alkaline resist.		5	3	5	4
Solvent resist.		5	4	5	3
Ethanol resist.		5	4	5	2

Rating standard: Light fastness 1(weak) \longrightarrow 8 (strong), others 1(weak) \longrightarrow 5(strong)

All rating test done within our laboratory

Version: BV-QESR-YMTA-TDS-124-C/1

Release date: 2022.07.25



【Index test description】

Test Item	Test conditions		
TV(Viscosity)	Viscometer, 400rpm,32±1°C		
Spreadmeter DM mm	Spreadmeter, 25±0.5°C		
Fineness GM μ	Grindometer		
Drying value DT min	Drying meter, ambient temperature		
Colour	Colour drawdown compare to standard		

[Disclaimer]

The data shown in this document is based on actual production and test result generated within our company. Above data is only for reference and does not bear any legal guarantee responsibilities. Whether actual ink performance can meet user's requirement depends on application conditions and substrate etc. We suggest that users should access whether current production conditions meet the application requirement of each product before printing. Since we cannot control the actual application and storage conditions, we cannot guarantee the final product performance. All product sales subject to our standard sales terms and conditions.

Version: BV-QESR-YMTA-TDS-124-C/1

Release date: 2022.07.25