



FV2-01 Series Bright Fast Drying Offset Printing Ink

【Product description】

FV2-01 series bright quick-drying offset printing ink is suitable for printing on substrates of coated paper, offset paper, ivory board, white board, etc. It is suitable for single-color and four-color printing on single paper offset presses.

【Characteristics】

- ❖ Has good fixability and drying performance.
- ❖ Appropriate fluidity and viscosity, good performance on the printing press.
- ❖ Bright colors, hue meet the ISO12647-2 standards, strong reproducibility of original color.

【Technical parameter】

Product	FV2101	FV2301	FV2401	FV2501
Index	BLACK	YELLOW	MAGENTA	CYAN
TV(Viscosity)	9-11	8-10	8-10	8-10
DM mm(Fluidity)	33-39	33-39	33-39	33-39
DT min(Drying time)	≤750	≤750	≤750	≤750

【Index test description】

Test Items	Test conditions
TV(Viscosity)	Viscometer, 400rpm, 32±1°C
DM mm(Fluidity)	Spread meter, 25±2°C
DT min(Drying time)	Dryer, ambient temperature
Color	Color drawdown, compared with standard sample

【Instructions】

- ❖ Can be used directly on the machine under normal circumstances. Varnish can be added if low ambient temperature or poor surface condition of printing paper. If you



have light fastness or other requirements, please choose our company's special products.

- ❖ Note: adding ratio of additive should not exceed 3%.

【Packaging and shelf life】

This product is packed in 1kg, 2kg and 200kg, and the shelf life is 3 years.

【Disclaimer】

The data shown in this document is based on actual production and test result generated within our company. Above data is only for reference and does not bear any legal guarantee responsibilities. Whether actual ink performance can meet user's requirement depends on application conditions and substrate etc. We suggest that users should access whether current production conditions meet the application requirement of each product before printing. Since we cannot control the actual application and storage conditions, we cannot guarantee the final product performance. All product sales subject to our standard sales terms and conditions.